

## Aplique IP44 MIRAM LED



### Características gerais

#### 1.0 LED

LED LED 9W | 220-240VAC  
PCB 3-step | incl. PS  
output selector | phase-cut dim  
aluminium powder coated  
opal PMMA cover

☑️ 📄 🧑 🗣️ 0.51kg ⚡ IP44 📏 ±0,3+D 📄

#### 2.0 LED

LED LED 12W | 220-240VAC  
PCB 3-step | incl. PS  
output selector | phase-cut dim  
aluminium powder coated  
opal PMMA cover

☑️ 📄 🧑 🗣️ 0.65kg ⚡ IP44 📏 ±0,3+D 📄

#### 3.0 LED

LED LED 18W | 220-240VAC  
PCB 3-step | incl. PS  
output selector | phase-cut dim  
aluminium powder coated  
opal PMMA cover

☑️ 📄 🧑 🗣️ 0.69kg ⚡ IP44 📏 ±0,3+D 📄

#### Light Colour Selection

	LUMEN	CRI	CODE
2700K	L 320 / H 560	>90	3
3000K	L 360 / H 620	>90	5

#### Light Colour Selection

	LUMEN	CRI	CODE
2700K	L 530 / H 820	>90	3
3000K	L 590 / H 900	>90	5

#### Light Colour Selection

	LUMEN	CRI	CODE
2700K	L 610 / H 1050	>90	3
3000K	L 680 / H 1150	>90	5

### Dimensões



